



Chloroprene rubber (CR) selection guide

The chloroprene rubber (CR) used in general industrial rubber products

Sundow SN	Modifier	Crystallization	Mooney Viscosity, ML(1+4)100 °C	Dupont, SDK Neoprene	Lanxess Baypren	Denka	Tosoh Skyprene	Main application
SNR121	Sulfur	Slow	30-50	GNA-M1 GS	510/611/711	PM-40 PM-40NS DCR-40	R22/R11	Mine conveyor belts, power transmission belts, hoses, seals, wire and cable jackets
SNR122	Sulfur	Slow	51-65	GNA-M2 GS	510/611/711	PM-40 PM-40NS DCR-40	R22/R11	
SNR123	Sulfur	Slow	66-75	---	---	---	---	
SNR231	Mercaptan	Medium	34-41	W-M1	211	M-30	B31	Extruded bars, hoses, tapes, rubber seals, wire and cable jackets
SNR232	Mercaptan	Medium	42-54	W/WB	210	M-40 M-41	B30 R30	
SNR233	Mercaptan	Medium	50-65	---	---	M-40 M-41/M-70	---	
SNR238	Mercaptan	Medium	90-110	WHV100	230	M-100	Y31	
SNR239	Mercaptan	Medium	111-130	WHV	230	M-120	Y30	
SNR321	Four sulfide+ Sulfur	Medium	34-49	GW	510/611/711	PM-40 PM-40NS DCR-40	505 P90	Mine conveyor belts, power transmission belts, hoses, seals, cushions, wire and cable jackets.
SNR322	Four sulfide+ Sulfur	Medium	50-60	---	510/611/711	PM-40 PM-40NS DCR-40	505 P90	
SNR323	Four sulfide+ Sulfur	Medium	60-70	---	---	----	---	